

C300 MKII Housing

Compact 4K. Travel-Light. "Bulletproof". Gates.



Glove fit. Like its compact predecessor C500, the new Gates C300 MKII Housing is designed specifically to close fit the Canon EOS C300 MKII camera. That means it's compact and travel friendly.

Cinema caliber. The C300 MKII Housing shares many features with its Gates cinema housing cousins including full camera and lens control, support for over 150 EF and PL mount lenses, External Monitor options, and Gates Precision ports for no-compromises image quality.

Capture Confidence. Gates 'bulletproof' durability is naturally inherent in the C300 MKII Housing. When failure is not an option, the C300 MKII Housing is ready.

Professionals know that failure is not an option, so they never take a chance.... they take a *Gates!*

Key Features



Durable, "Bulletproof" machined aluminum, black type III 'hard' anodize finish, and sealed with a nickel-acetate process.



Clean. Uncomplicated. User friendly controls are 100% mechanical. No complex mechanisms. *Simplicity = Reliability.*



Included Starlite ST5 External Monitor. Other external monitors like EM43 and TVL55 are optional.




Grip it your way. Adjust the handle grips to fit your hand / glove and perfect control access.



Flexible Lens Support. The C300 MKII is designed to accommodate a wide variety of EF and PL mount lenses.



2-Year Warranty. Only Gates offers a 2-year renewable warranty on all housings.



Fully Adjustable Buoyancy and Trim. Add / remove trim weights for ideal balance -- just the way you like it.



FIZ control made easy. Set the Focus / Iris / Zoom knobs just the way you like: close, mid or stacked. Fine lens adjustments were never easier.



Precision Ports™ means clarity, sharpness and no vignetting (cutoff dark corners) to spoil your images.



Seal Check II (included) assures housing integrity *before* entering the water.

Specifications

* Controls (All Mechanical)

- * Power
- * Zoom
- * Assign 1&2
- * Select/Set
- * Menu
- * Record/Standby
- * Focus
- * Assign 3&4
- * WB Set/Playback
- * Cancel
- * Iris
- * ND Filter
- * Function/Backlight

* Dimensions

- * Basic Shell (transport size SP80 dome)
 - * 13.8" L x 8.7" H x 8.6" W
 - * 35 cm x 22 cm x 21.8 cm
- * Fully Assembled (+monitor, handles, 8" dome)
 - * 12.8" L x 16" H x 13.1" W
 - * 35 cm x 24 cm x 33.2 cm

* Depth Rating

- * 300 feet / 92 meters

* Construction

- * Machined Aluminum, Type III 'Hard' Anodize finish. Stainless steel hardware.

* Weight in Air

- * Transport (housing + SP80 Glass Dome)
20.3 lbs / 9.2 kg

* Weight in Water

- * Fully adjustable buoyancy / trim.

* Batteries

- * Canon BP-A30 or BP-A60.
- * TBD Battery required to use Starlite ST5 External Monitor

* Warranty

- * 2 Years Renewable.

Port Options



Standard Dome Port SP80-8 or SP80-10

Optical glass with AR coating provides clear, sharp images for DSLR and cinema glass.



Flat Port FP80

A simple flat element good for macro work. Element is field replaceable.

Accessories (Preliminary)



GT14 LED Lights

14,000 lumens *and* 90 CRI underwater illumination for natural history and cinema productions.



HD-SDI Surface Feed, Water Alarm, Tripod Mount and more.

Supported Lenses [as of 2-2016]

Over 150 lenses are supported in C300 MKII

- Cine Primes
- Cine Zooms
- Anamorphics
- Canon DSLR
- DSLR Conversions

Don't Take a Chance....Take a *Gates!*

Gates Underwater Products, Inc

13685 Stowe Dr. Suite A • Poway, CA • 92064 • (858) 391-0052 • Fax (858) 391-0053 • GatesHousings.com